

## CTL-ENOC-XX LED

(W)			IP	(Vac)	x10 = mA)
40	LUD-040S	DSF	IP20	90 ~ 305	075,150
60	LUD-060S	DSF	IP20	90 ~ 305	055, 078, 110, 150, 210
96	ESD-096S	DT	-	249 ~ 528	090, 180, 360
150	EUD-150S	DT/DV	IP67	90 ~ 305	130, 260, 520
150	EUD-150S	DTA/DVA	IP67	90 ~ 305	105, 210, 350, 560
150	ESD-150S	DT	-	249 ~ 528	105, 210, 350, 560
200	EUD-200S	DD/DT/DV	IP67	90 ~ 305	070, 105, 140, 210, 245, 280, 420, 490
240	EUD-240S	DT/DV	IP67	90 ~ 305	100, 150, 220, 320, 460, 660
240	ESD-240S	DT	-	249 ~ 528	100, 150, 220, 320, 460, 660
320	EUD-320S	DT/DV	IP67	90 ~ 305	150, 220, 320, 460, 670
320	ESD-320S	DT	-	249 ~ 528	150, 220, 310, 440, 620
600	EUD-600S	DT/DV	IP67	90 ~ 305	140, 280, 420, 560, 740, 980, 12A

# INVENTRONICS

CTL-ENOC-XX

Rev. B

---

2016-12-08	A	/	/	/
2018-01-12	B	/		